Eltex UPG yarn break detector

16720/16730

The UPG is a small, general purpose, thread break detector. It operates on the piezoelectric principle, detecting the yarn movement. This working principle makes it suitable for all types of yarn and makes it insensitive to dust, dirt and humidity variations.

The detector has an optocoupler output suitable for PLC or other electronic control devices.

A LED (light emitting diode) indicates the yarn movement.

The ceramic sensor part can be used either as a closed eyelet or as an open bar.

Several detectors can be connected in parallel.



Function description

Sensing part Aluminium oxide ceramic, with a Ø3 mm closed

eyelet and a 7 mm wide bar.

Output Optocoupler, active when yarn is **not moving**.

Sensitivity setting The sensitivity can be adjusted with a potentio-

meter under the lid.

The output reflects the movement of the yarn. When the yarn is moving, the optocoupler is inactive. When the yarn is not moving, the optocoupler is active.

The LED is on when the yarn is moving.

The detector is supplied with cable and a 6/4 modular plug connector. Many thread detectors can be connected in parallel. The detector is protected against wrong polarity on power supply.

Application examples

- Winders
- Spinning machines
- Twisters
- Texturing machines
- Sewing machines
- Covering machines
- Yarn preparation machines
- Double/multiple picks on airjet weaving machines





■ Technical specifications

Housing in zinc metal

Power supply 15–30 V DC

Current consumption 20 mA

Output:

Max. switching current 10 mA Max. voltage drop 2 V Reaction time 150 ms


Cable length


16720 0.5 m 16730 3.5 m


Cable connector 6/4 modular plug connector




■ Dimensions (mm)










Yarn direction possibilities





Box 24, SE-283 21 OSBY, Sweden | Tel: +46 479 536300 | Fax: +46 479 536399 | Email: info@eltex.se | www.eltex.se